



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

EPD HUB, HUB-6584

Published on 05.06.2026, last updated on 05.06.2026, valid until 05.06.2031

**30MPA-OPC+50%GGBFS+10%MS@56Days-200±40mm slump-
20mm Agg-CY**

Saudi Readymix Concrete Co, Joint Stock Company Unlisted



This EPD is intended for business-to-business and/or business-to-consumer communication. Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

MANUFACTURER AND SITE

Manufacturer	Saudi Readymix Concrete Co, Joint Stock Company Unlisted
Address	2nd Industrial City, Dammam - Kingdom of Saudi Arabia - P.O Box 8635 - 34333 - Dammam - SA
Contact details	info@saudireadymix.com.sa
Website	www.saudireadymix.com.sa
Place of production	Saudi Arabia - Eastern Region
Place(s) of raw material origin	Saudi Arabia - Eastern Region
Place(s) of installation and use	Saudi Arabia - Eastern Region
Period for data	1.1.2024 - 31.12.2024

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR version 1.2, 24 Mar 2025
cPCR	EN 16757 Product Category Rules for concrete and concrete elements
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	
Scope of the EPD	Cradle to gate with options, A4-A5, and modules C1-C4, D
EPD author	Khaldoon Slaiai - Saudi Readymix
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☒ External verification
EPD verifier	Haiha Nguyen as an authorized verifier for EPD Hub

PRODUCT SPECIFICATION

Product name	30MPA-OPC+50%GGBFS+10%MS@56Days-200±40mm slump-20mm Agg-CY
Product reference	0108-AMMZMFCA003
Concrete type	Ready-mix concrete
Product standards	EN 206
Additional characteristic	
GTIN (Global Trade Item Number)	-
NOBB (Norwegian Building Product Database)	-
A1-A3 Specific data (%)	12,2

PRODUCT DESCRIPTION

0108-AMMZMFCA003-(30MPA-OPC+50%GGBFS+10%MS@56Days-200±40mm slump-20mm Agg-CY)

Project: Al-Mosa Hospital - Hafouf

Type of Structure: Concrete for Raft Foundation

Cementitious Materials: OPC+50%GGBFS+10%MS

ABOUT THE MANUFACTURER PRODUCT CHARACTERISTICS

Compressive strength class:

C16/20

Strength evaluation days:

28 days

Exposure class:

XD2

XC2

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 cubic meter
Declared unit mass, kg	2365
GWP-total, A1-A3 (kg CO ₂ e)	206
GWP-fossil, A1-A3 (kg CO ₂ e)	206
Secondary material, inputs (%)	0,01
Secondary material, outputs (%)	70
Total energy use, A1-A3 (kWh)	415
Net freshwater use, A1-A3 (m ³)	1,39E+00

LIFE CYCLE ASSESSMENT

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Beyond the system boundaries	D	x	Reuse, Recovery, Recycling
	C4	x	Disposal
End of life stage	C3	x	Waste processing
	C2	x	Transport
	C1	x	Deconstr./demol.
	B7	N D	Operational water
Use stage	B6	N D	Operational energy
	B5	N D	Refurbishment
	B4	N D	Replacement
	B3	N D	Repair
	B2	N D	Maintenance
	B1	N D	Use
	A5	x	Assembly
	A4	x	Transport
Product stage	A3	x	Manufacturing
	A2	x	Transport
	A1	x	Raw materials

Not declared = ND.

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Not applicable
Ancillary materials	Physical Properties
Manufacturing energy and waste	Physical Properties

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	No grouping
Grouping method	Not applicable
Variation in GWP-fossil for A1-A3, %	0

This EPD is product and factory specific.

PRODUCT RAW MATERIAL MAIN COMPOSITION

The product is a ready-mix concrete consisting of aggregates, cement, filler, admixtures, and water. Main material categories as per EPD Hub GPI are shown below:

Raw material category	Amount, mass- %	Material origin
Metals	0	-
Minerals	93,6	Saudi Arabia
Fossil materials	0,10	Saudi Arabia
Bio-based materials	0	-

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
--	---

PRODUCT LIFE CYCLE

MANUFACTURING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.


A market-based approach is used in modelling the electricity mix utilized in the factory.

The use of green energy in manufacturing is demonstrated through contractual instruments (GOs, RECs, etc.), and its use is ensured throughout the validity period of this EPD.

Ready-mix concrete production starts by transporting the binders, aggregates, and additives to the manufacturing site and storing them into closed silos and containers. The aggregates are then dosed onto a scale and transferred to a concrete mixer. In the mixer, cement is added to the aggregates, after which the material is mixed dry. Water and additives are then added to the mixture, followed by wet mixing. After mixing, the concrete mass is unloaded from the mixer into the tank of the concrete mixer truck, which is transported to the construction site.

No packaging is included as the product is transported with mixer trucks.

MANUFACTURING PROCESS DIAGRAM (A1-A3)



TRANSPORT AND INSTALLATION (A4-A5)

The concrete is transported to the building site using an average lorry. Transportation impacts occurred from final products delivery to construction site cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions (A4).

Installation includes the energy used for concrete application. This consists of the energy spent by a concrete mixer truck and a concrete pump. A production loss of 3 % at installation is assumed (A5).

PRODUCT END OF LIFE (C1-C4, D)

At the end of its life, the concrete is assumed to be part of a concrete building that is demolished using machinery, consuming energy in the form of diesel (C1).

The concrete blocks gotten after the demolition are delivered 50 km by a lorry to the nearest construction waste treatment (C2). It is assumed that 100% of the demolished concrete is transported to a site where this waste is processed by, crushing the blocks to gravel. About 70% of concrete can be recycled this way (C3), with an assumption that non-reinforced concrete is being sorted. The remaining 30% of concrete is assumed to be sent to the landfill for disposal (C4). The crushed concrete received from waste treatment can be used as a replacement for virgin gravel or for raw materials in road construction (D). The process losses of the waste treatment plant are assumed to be negligible.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA Concrete EPD Generator v3.2.4. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent v3.10.1/3.11/3.12 and One Click LCA databases were used as sources of environmental data. Allocation used in Ecoinvent 3.10.1/3.11/3.12 environmental data sources follow the methodology 'allocation, cut-off, EN 15804+A2'.

ENVIRONMENTAL IMPACT DATA

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	1,81E+02	1,90E+01	6,21E+00	2,06E+02	9,46E+00	1,46E+01	ND	ND	ND	ND	ND	ND	ND	4,50E+00	1,27E+01	7,24E+00	4,43E+00	-1,33E+01
GWP – fossil	kg CO ₂ e	1,81E+02	1,90E+01	6,21E+00	2,06E+02	9,46E+00	1,46E+01	ND	ND	ND	ND	ND	ND	ND	4,50E+00	1,27E+01	7,24E+00	4,43E+00	-1,32E+01
GWP – biogenic	kg CO ₂ e	0,00E+00	4,31E-03	3,57E-04	4,67E-03	2,17E-03	4,94E-03	ND	ND	ND	ND	ND	ND	ND	4,59E-04	2,88E-03	-7,39E-04	-1,41E-03	-4,16E-02
GWP – LULUC	kg CO ₂ e	1,33E-01	8,51E-03	1,11E-04	1,41E-01	4,21E-03	5,39E-03	ND	ND	ND	ND	ND	ND	ND	4,61E-04	5,69E-03	7,42E-04	2,53E-03	-1,84E-02
Ozone depletion pot.	kg CFC-11e	1,00E-06	2,81E-07	5,76E-07	1,86E-06	1,37E-07	1,86E-07	ND	ND	ND	ND	ND	ND	ND	6,89E-08	1,88E-07	1,11E-07	1,28E-07	-1,11E-06
Acidification potential	mol H ⁺ e	6,23E-01	6,49E-02	2,40E-02	7,12E-01	3,29E-02	9,31E-02	ND	ND	ND	ND	ND	ND	ND	4,06E-02	4,34E-02	6,54E-02	3,14E-02	-8,67E-02
EP-freshwater ²⁾	kg Pe	2,12E-02	1,50E-03	8,23E-05	2,28E-02	1,02E-03	9,73E-04	ND	ND	ND	ND	ND	ND	ND	1,30E-04	9,91E-04	2,09E-04	3,64E-04	-7,85E-04
EP-marine	kg Ne	1,75E-01	2,13E-02	5,00E-03	2,02E-01	1,09E-02	3,89E-02	ND	ND	ND	ND	ND	ND	ND	1,88E-02	1,43E-02	3,03E-02	1,20E-02	-1,88E-02
EP-terrestrial	mol Ne	2,02E+00	2,32E-01	5,46E-02	2,31E+00	1,18E-01	4,29E-01	ND	ND	ND	ND	ND	ND	ND	2,06E-01	1,55E-01	3,32E-01	1,31E-01	-2,45E-01
POCP (“smog”) ³⁾	kg NMVOCe	5,68E-01	9,57E-02	1,64E-02	6,80E-01	4,82E-02	1,29E-01	ND	ND	ND	ND	ND	ND	ND	6,15E-02	6,40E-02	9,90E-02	4,68E-02	-6,29E-02
ADP-minerals & metals ⁴⁾	kg Sbe	8,98E-04	5,31E-05	2,01E-07	9,52E-04	2,71E-05	3,34E-05	ND	ND	ND	ND	ND	ND	ND	1,61E-06	3,55E-05	2,60E-06	7,04E-06	-1,33E-04
ADP-fossil resources	MJ	1,09E+03	2,76E+02	9,51E+01	1,46E+03	1,35E+02	1,56E+02	ND	ND	ND	ND	ND	ND	ND	5,89E+01	1,85E+02	9,48E+01	1,09E+02	-1,97E+02
Water use ⁵⁾	m ³ e depr.	4,35E+01	1,37E+00	3,35E+01	7,83E+01	7,87E-01	2,66E+00	ND	ND	ND	ND	ND	ND	ND	1,47E-01	9,12E-01	2,37E-01	3,14E-01	-2,62E+01

1) GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	7,14E-06	1,90E-06	2,09E-07	9,25E-06	9,26E-07	2,68E-06	ND	ND	ND	ND	ND	ND	ND	1,15E-06	1,27E-06	1,42E-05	7,15E-07	-1,11E-06
Ionizing radiation ⁶⁾	kBq U235e	5,01E+04	2,40E-01	6,07E-02	5,01E+04	1,13E-01	1,50E+03	ND	ND	ND	ND	ND	ND	ND	2,61E-02	1,61E-01	4,20E-02	6,83E-02	-3,13E+00
Ecotoxicity (freshwater)	CTUe	3,58E+02	3,98E+01	1,20E+00	3,99E+02	2,80E+01	1,93E+01	ND	ND	ND	ND	ND	ND	ND	3,24E+00	2,61E+01	5,22E+00	9,12E+00	-2,36E+02
Human toxicity, cancer	CTUh	5,21E-08	3,13E-09	1,96E-10	5,54E-08	1,48E-09	2,58E-09	ND	ND	ND	ND	ND	ND	ND	4,63E-10	2,10E-09	7,45E-10	8,17E-10	-1,37E-08
Human tox. non-cancer	CTUh	1,21E-06	1,78E-07	1,32E-08	1,40E-06	8,39E-08	6,10E-08	ND	ND	ND	ND	ND	ND	ND	7,33E-09	1,20E-07	1,18E-08	1,88E-08	-2,52E-07
SQP ⁷⁾	-	9,31E+02	2,78E+02	4,50E+00	1,21E+03	1,35E+02	5,94E+01	ND	ND	ND	ND	ND	ND	ND	4,12E+00	1,86E+02	6,64E+00	2,14E+02	-1,90E+02

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator. 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	5,46E+01	3,78E+00	2,71E-01	5,87E+01	1,88E+00	2,55E+00	ND	ND	ND	ND	ND	ND	ND	3,73E-01	2,53E+00	6,00E-01	1,05E+00	-1,95E+01
Renew. PER as material	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of renew. PER	MJ	5,46E+01	3,78E+00	2,71E-01	5,87E+01	1,88E+00	2,55E+00	ND	ND	ND	ND	ND	ND	ND	3,73E-01	2,53E+00	6,00E-01	1,05E+00	-1,95E+01
Non-re. PER as energy	MJ	1,06E+03	2,76E+02	9,57E+01	1,43E+03	1,35E+02	1,55E+02	ND	ND	ND	ND	ND	ND	ND	5,89E+01	1,85E+02	9,48E+01	1,09E+02	-2,03E+02
Non-re. PER as material	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of non-re. PER	MJ	1,06E+03	2,76E+02	9,57E+01	1,43E+03	1,35E+02	1,55E+02	ND	ND	ND	ND	ND	ND	ND	5,89E+01	1,85E+02	9,48E+01	1,09E+02	-2,03E+02
Secondary materials	kg	2,89E-01	0,00E+00	0,00E+00	2,89E-01	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Renew. secondary fuels	MJ	4,96E-03	1,49E-03	3,33E-06	6,46E-03	7,37E-04	3,71E-04	ND	ND	ND	ND	ND	ND	ND	6,39E-05	9,99E-04	1,03E-04	5,66E-04	-1,57E-03
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m ³	1,35E+00	4,07E-02	9,82E-04	1,39E+00	1,94E-02	5,31E-02	ND	ND	ND	ND	ND	ND	ND	3,89E-03	2,73E-02	6,26E-03	1,13E-01	-6,10E-01

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	5,62E+00	5,19E-01	1,09E-03	6,14E+00	8,63E-01	3,34E-01	ND	ND	ND	ND	ND	ND	ND	6,55E-02	3,13E-01	1,05E-01	1,20E-01	-1,54E+00
Non-hazardous waste	kg	1,16E+02	9,69E+00	4,17E-02	1,26E+02	1,70E+01	6,06E+00	ND	ND	ND	ND	ND	ND	ND	8,93E-01	5,79E+00	1,44E+00	2,74E+00	-2,84E+01
Radioactive waste	kg	5,37E-04	5,87E-05	8,85E-06	6,04E-04	2,71E-05	3,14E-05	ND	ND	ND	ND	ND	ND	ND	6,40E-06	3,94E-05	1,03E-05	1,67E-05	-3,92E-04

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	6,08E-10	0,00E+00	3,31E+00	3,31E+00	0,00E+00	4,98E+01	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	1,66E+03	0,00E+00	0,00E+00
Materials for energy rec	kg	3,18E-18	0,00E+00	0,00E+00	3,18E-18	0,00E+00	9,55E-20	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy: Electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy: Heat	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	1,80E+02	1,89E+01	6,19E+00	2,05E+02	9,40E+00	1,45E+01	ND	ND	ND	ND	ND	ND	ND	4,48E+00	1,27E+01	7,21E+00	4,39E+00	-1,64E+01
Ozone depletion Pot.	kg CFC-11e	8,74E-07	2,24E-07	5,01E-07	1,60E-06	1,10E-07	1,51E-07	ND	ND	ND	ND	ND	ND	ND	5,46E-08	1,50E-07	8,79E-08	1,02E-07	-1,13E-07
Acidification	kg SO ₂ e	4,67E-01	4,96E-02	1,97E-02	5,36E-01	2,51E-02	6,67E-02	ND	ND	ND	ND	ND	ND	ND	2,86E-02	3,31E-02	4,60E-02	2,32E-02	-7,88E-02
Eutrophication	kg PO ₄ ³ e	5,00E-01	1,21E-02	2,28E-03	5,15E-01	6,79E-03	2,74E-02	ND	ND	ND	ND	ND	ND	ND	6,67E-03	8,08E-03	1,07E-02	7,39E-03	-1,55E-02
POCP (“smog”)	kg C ₂ H ₄ e	3,56E-02	4,42E-03	8,93E-04	4,10E-02	2,18E-03	5,06E-03	ND	ND	ND	ND	ND	ND	ND	2,14E-03	2,95E-03	3,45E-03	2,20E-03	-7,02E-03
ADP-elements	kg Sbe	6,17E-04	5,18E-05	1,99E-07	6,69E-04	2,63E-05	2,47E-05	ND	ND	ND	ND	ND	ND	ND	1,57E-06	3,46E-05	2,52E-06	6,90E-06	-9,00E-05
ADP-fossil	MJ	1,06E+03	2,72E+02	9,51E+01	1,42E+03	1,33E+02	1,54E+02	ND	ND	ND	ND	ND	ND	ND	5,84E+01	1,82E+02	9,41E+01	1,08E+02	-2,03E+02

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e	1,81E+02	1,90E+01	6,21E+00	2,06E+02	9,46E+00	1,46E+01	ND	ND	ND	ND	ND	ND	ND	4,50E+00	1,27E+01	7,24E+00	4,43E+00	-1,33E+01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation – A3 (Energy data source)

1. Electricity, Electricity, consumption mix w/o renewables, Saudi Arabia, 2023, Saudi Arabia, LCA study for country specific consumption mixes, OneClickLCA 2025, 0.65 kgCO₂e/kWh

Installation scenario documentation - A5 (Diesel consumption)

1. Diesel, burned in building machine, World, ecoinvent 3.10.1, 0.1 kg CO₂e/MJ

TRANSPORT SCENARIO DOCUMENTATION - A4

Scenario parameter	Value
Vehicle type used for transport (e.g., long distance truck, boat, etc.) / Vehicle type, Commission Directive 2007/37/EC (European Emission Standard)	Concrete mixer truck
Distance, km	36
Capacity utilisation (including empty return) %	50 %
Bulk density of transported products / kg/m ³	2370
Volume capacity utilisation factor (factor: =1 or <1 or ≥1 for compressed or nested packaged products)	1

INSTALLATION SCENARIO DOCUMENTATION - A5

Scenario parameter	Value
Ancillary materials for installation (specified by material) / kg or other units as appropriate	0
Water use / m ³	0
Other resource use / kg	0
Waste materials on the building site before waste processing, generated by the product's installation (specified by type) / kg	71
Output materials as result of waste processing at the building site e.g. collection for recycling / kg	49,7
Output materials as result of waste processing at the building site e.g. collection for disposal / kg	21,3
Direct emissions to ambient air, soil and water / kg	0

END OF LIFE SCENARIO DOCUMENTATION

Scenario information	Value
Collection process – kg collected separately	0
Collection process – kg collected with mixed construction waste	2365
Recovery process – kg for re-use	0
Recovery process – kg for recycling	1660
Recovery process – kg for energy recovery	0
Disposal (total) – kg for final deposition	710
Scenario assumptions e.g. transportation	Market for transport, freight, lorry >32 metric ton, EURO5; 50km

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.



Program assistant: Xinyuan Zhang



The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

[Verified tools](#)

Tool verifier: Imane Uald Lamkaddam

Tool verification validity: 28 March 2025 - 27 March 2028