



Building
something
great

Environmental Product Declaration
IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Environmental Product Declaration

32 MPa Low Shrinkage Concrete

Melbourne



EPD HUB, HUB-5881

Published on 27.03.2026, last updated on 27.03.2026, valid until 26.03.2031



In accordance with EN 15804+A2 & ISO 14025 / ISO 21930

Contents

Environmental Product Declaration	1
General information	3
<i>Manufacturer and site</i>	<i>3</i>
<i>EPD standards, scope and verification</i>	<i>3</i>
<i>Product specification</i>	<i>4</i>
<i>Product characteristics</i>	<i>4</i>
<i>Environmental data summary.....</i>	<i>4</i>
Life cycle assessment.....	5
<i>System boundaries</i>	<i>5</i>
<i>Cut-off criteria</i>	<i>5</i>
<i>Validation of Data</i>	<i>5</i>
<i>Allocation, estimates and assumptions</i>	<i>6</i>
<i>Product & manufacturing sites grouping</i>	<i>6</i>
<i>Product raw material main composition</i>	<i>6</i>
<i>Substances, REACH – very high concern.....</i>	<i>6</i>
<i>Biogenic carbon content.....</i>	<i>6</i>
About Boral	7
Product life-cycle.....	11
<i>Manufacturing (A1-A3)</i>	<i>11</i>
<i>Transport and installation (A4-A5).....</i>	<i>11</i>
<i>Product use and maintenance (B1-B7)</i>	<i>11</i>
<i>Product end-of-life (C1-C4, D).....</i>	<i>11</i>
<i>System Diagram</i>	<i>12</i>
<i>LCA software and bibliography</i>	<i>12</i>
Environmental impact data.....	13
<i>Core environmental impact indicators – EN 15804+A2, EF 3.1.....</i>	<i>13</i>
<i>Additional environmental impact indicators – EN 15804+A2, EF 3.1.....</i>	<i>14</i>
<i>Use of natural resources</i>	<i>15</i>
<i>End of life – Waste</i>	<i>16</i>
<i>End of life – Output flows.....</i>	<i>17</i>
<i>Environmental impacts – EN 15804+A1, CML / ISO 21930</i>	<i>17</i>
<i>Additional indicator – GWP-GHG</i>	<i>18</i>
Scenario documentation.....	19
Third-party verification statement	20

General information

Manufacturer and site

Manufacturer	Boral Limited
Address	Level 3, Trinité 2, 39 Delhi Rd, North Ryde NSW, AU
Contact details	sustainability@boral.com.au
Website	www.boral.com.au
Place of production	Melbourne
Place(s) of raw material origin	Australia
Place(s) of installation and use	Australia
Period for data	FY25

EPD standards, scope and verification

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR version 1.2, 24 Mar 2025
cPCR	EN 16757 Product Category Rules for concrete and concrete elements
Sector	Construction product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle-to-gate (A1-3) with modules C1-4, D
EPD author	Naomi Foster (Boral Construction Materials Ltd)
EPD verification	Independent verification of this EPD and data, according to ISO 14025: <input type="checkbox"/> Internal verification <input checked="" type="checkbox"/> External verification
EPD verifier	Vera Durão, as an authorised verifier acting for EPD Hub Limited

Product specification

Product name	32 MPa Low Shrinkage Concrete
Concrete type	Ready-mix concrete
Product standards	AS 1379 Specification and supply of concrete
Product description	Low shrinkage concrete has been designed to have minimal volume change over the curing process, reducing cracking and structural issues. This concrete is produced in accordance with AS 1379-2007 Specification and supply of concrete. This concrete is produced with a strength class of S32. It is designed for low shrinkage in special engineering applications.
A1-A3 Specific data (%)	99

Product characteristics

Compressive strength class:
S32

Strength evaluation days:
28 days

This EPD is intended for business-to-business and/or business-to-consumer communication. Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterisation factors EF 3.1. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

Environmental data summary

Declared unit	1 cubic metre
Declared unit mass, kg	2318
GWP-total, A1-A3 (kg CO₂e)	2.73E+02
GWP-fossil, A1-A3 (kg CO₂e)	2.73E+02
Secondary material, inputs (%)	0
Secondary material, outputs (%)	70
Total energy use, A1-A3 (kWh)	416
Net freshwater use, A1-A3 (m³)	7.44E+00

Life cycle assessment

System boundaries

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	ND	ND	ND	ND	ND	ND	ND	ND	ND	x	x	x	x	x	x	x
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = ND

Cut-off criteria

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

Validation of Data

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterisation factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

Allocation, estimates and assumptions

All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Not applicable
Ancillary materials	Allocated by mass
Manufacturing energy and waste	Allocated by mass

This EPD covers a single product that may exhibit minor variations in composition. These variations may include differences in slump, aggregate size, and other minor differences. Boral has verified that the variation in Global Warming Potential (GWP) across all covered variants remains within $\pm 10\%$. However, for environmental impact categories with relatively small absolute impacts, percentage variations may exceed 10%. This is due to small absolute differences resulting in proportionally larger percentage changes. For further information regarding product variations, please contact the manufacturer.

Product & manufacturing sites grouping

Type of grouping	Multiple sites
Grouping method	Based on average results of product group - by total volume
Variation in GWP-fossil for A1-A3, %	Variation in GWP for modules A1-A3 is -0.4% to 1.4%

This EPD is declared as a single product manufactured at multiple sites in the Melbourne metropolitan region of Victoria. These sites are grouped together on the basis of having the same supply chain and major production steps. Results are averaged by production volume across the sites. There are 8 sites covered in this region: Deer Park, Tullamarine, Somerton, Sunbury, Wollert, Melton, West Melbourne, and West Melbourne (wet)

Product raw material main composition

The product is a ready-mix concrete consisting of aggregates, cement, filler, admixtures, and water. Main material categories as per EPD Hub GPI are shown below:

Raw material category	Amount, mass- %	Material origin
Metals	0	-
Minerals	100	Australia
Fossil materials	0	-
Bio-based materials	0	-

Substances, REACH – very high concern

The product does not contain any REACH SVHC substances in amounts greater than 0.1 % (1000 ppm).

Biogenic carbon content

This product does not contain any biogenic carbon content in amounts greater than 5%.

About Boral

Boral is Australia's largest vertically-integrated construction materials company. That means we not only supply customers with outstanding raw materials like aggregate and sand, we also develop and produce advanced construction materials and solutions like low-carbon concretes and advanced asphalts.

Our network includes prized quarry and cement infrastructure, bitumen, construction materials recycling, asphalt and concrete batching operations. We work year-round to help customers deliver high-profile civil works and major infrastructure projects, as well as key residential, commercial and industrial developments.

We employ about 7,500 employees and contractors working in research, production and business support across more than 360 locations nationwide.


For nearly 80 years, we've been building something great in Australia. From the surface of the Sydney Harbour Bridge to the walls of Melbourne's Metro Tunnel, from the asphalt at Adelaide Airport right through to much of the concrete used in Brisbane's Gateway Bridge and Perth's Forrestville Airport Link, Boral has been making history around Australia.

Boral concrete has over 200 pre-mix concrete plants around Australia producing a wide range of concrete mixes in metropolitan and country areas. Boral concrete supplies pre-mix concrete to all segments of the construction industry including infrastructure, social, commercial and residential construction.


Construction materials Leading integrated network

360

Operating sites*




* Includes transport, fly ash and research and development sites.



Our integrated network

Valuable upstream and downstream operations with market leadership.

Boral moves ~50 million tonnes of products per year across its network



A lower carbon concrete product for every option

Boral's range of lower carbon concrete products will help you achieve your sustainability, engineering and architectural goals.

Boral Concrete's Lower Carbon Concrete (LCC) products can be used for all types of structures including:

- houses
- commercial buildings
- multi-residential buildings
- high-rise buildings
- civil projects, and
- infrastructure projects.

By matching the engineering properties of each product with the structural requirements, the carbon footprint of the project can be reduced for the optimal cost.

Traditional lower carbon concrete products have low early age strength and may have higher drying shrinkage which makes them less desirable for many applications. In particular, they are unsuitable for precast elements and post tensioned slabs.

Boral's Lower Carbon Concrete (LCC) products include products with good early age strength and superior engineering properties. They can be used for precast and post tensioned slabs so there is no compromise to the construction schedule and engineers can take advantage of the superior drying shrinkage properties.

Boral has three product ranges: ENVIROCRETE®, ENVIROCRETE® PLUS and ENVISIA®. ENVIROCRETE® concrete is a traditional lower carbon concrete product, Envirocrete® plus has better early age strength and drying shrinkage properties and Envisia® concrete has the best early age strength and drying shrinkage properties.

ENVISIA® concrete also has a light colour and exhibits a very good appearance in an off-formwork finish.

**Lower carbon concrete products
For all types of Structures**



Lower carbon concrete products

For all types of structures



Residential



Commercial



Multi-residential



High-rise



Civil



Infrastructure

ENVIROCRETE® products

Are suitable for all general applications where good early age strength and low drying shrinkage are not required.



- Low portland cement.
- Low embodied carbon.
- General applications.
- Suitable for projects targeting a GBCA¹ or ISC² rating.
- Low portland cement.
- Low embodied carbon.
- General applications.
- Suitable for projects targeting a GBCA¹ or ISC² rating.

ENVIROCRETE® PLUS products

Have good early age strength and can be used for some post tensioned applications. They also have good drying shrinkage characteristics which will comply with the shrinkage requirements in most engineering specifications.



- Low portland cement.
- Low embodied carbon.
- Low drying shrinkage.
- Good early age strength, suitable for most standard post tension applications.
- Suitable for projects targeting a GBCA¹ or ISC² rating.

ENVISIA® products

Have excellent early age strength and drying shrinkage characteristics.

They can be used for all standard post tensioned concrete applications and their low shrinkage characteristics provides engineers and architects with more design options. They have a light colour which provides architectural benefits, and they have excellent resistance to chloride ingress making them suitable for marine environments.



- Low portland cement.
- Low embodied carbon.
- Very low drying shrinkage.
- Good early age strength, suitable for all standard post tension applications.
- Very low drying shrinkage.
- Excellent resistance to chloride ingress.
- Light colour provides architectural benefits.
- Suitable for projects targeting a GBCA¹ or ISC² rating.

Environmental properties

Reduction in Portland cement^{3,4,5}	30% - 70%	45% - 70%	50% - 70%
Reduction in embodied carbon⁶	● ● ● ●	● ● ● ●	● ● ● ●

Engineering and durability properties

Early age strength	●	● ●	● ● ●
Drying shrinkage	●	● ● ●	● ● ● ●
Durability in a marine environment	● ●	● ● ●	● ● ● ●

¹ Green Building Council of Australia (GBCA). ² Infrastructure Sustainability Council (ISC). ³ Using the reference case from the GBCA Design and As-Built v1.3 rating tool. ⁴ The portland cement reductions in the table do not apply to Tasmania. Please contact the Boral Tasmanian office. ⁵ For specific values contact the local Boral office. ⁶ The dots indicate the relative reduction in embodied carbon. The hollow dots represent the potential relative reduction in embodied carbon. Contact the local Boral office for specific embodied carbon values. Alternatively, they can be found in Boral's Environmental Product Declarations which can be downloaded from boral.com.au/EPDs.

Product life-cycle

Manufacturing (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission and transformation. A market-based approach is used in modelling the electricity mix utilised in the batch plant.

Ready-mix concrete production starts by transporting the binders, aggregates, and additives to the manufacturing site and storing them into closed silos and containers. The considered transportation impacts include exhaust emissions resulting from transportation of raw materials from suppliers to manufacturing facilities as well as the environmental impacts of the production of the fuel used. The manufacturing, maintenance and disposal of the vehicles as well as tyre and road wear during transportation have also been included. The transportation distances and methods are based on the known supply chain for this product using information collected from local Boral teams, including road, rail and shipping. Where multiple manufacturing sites are being grouped, distances are averaged across the sites.

The aggregates are dosed onto a scale and transferred to a concrete mixer. In the mixer, cement is added to the aggregates, after which the material is mixed dry. Water and additives are then added to the mixture, followed by wet mixing. After mixing, the concrete mass is unloaded from the mixer into the tank of the concrete agitator truck, which is transported to the construction site.

No packaging is included as the product is transported with mixer trucks.

Transport and installation (A4-A5)

Installation includes the energy used for concrete application. This consists of the energy spent by a concrete mixer truck and a concrete pump.

Modules not declared.

Product use and maintenance (B1-B7)

This EPD does not cover the use phase. Air, soil, and water impacts during the use phase have not been studied. Carbonation is not taken into account in this EPD.


Modules not declared.

Product end-of-life (C1-C4, D)

At the end of its life, the concrete is assumed to be part of a concrete building that is demolished using machinery, consuming energy in the form of diesel (C1).

The concrete recovered after demolition is delivered 50 km by truck to the nearest construction waste treatment site (C2). It is assumed that 100% of the demolished concrete is transported to a site where this waste is processed by crushing the blocks to gravel. About 70% of concrete can be recycled this way (C3), with an assumption that non-reinforced concrete is being sorted (Gervasio, H. and Dimova, S., 2018. Model for Life Cycle Assessment (LCA) of buildings. European Commission, Joint Research Centre.). The remaining 30% of concrete is assumed to be sent to the landfill for disposal (C4). The crushed concrete received from waste treatment can be used as a replacement for virgin gravel or for raw materials in road construction (D). The process losses of the waste treatment plant are assumed to be negligible.

System Diagram



This system shows the system boundary with dashed lines and shows included modules in green, while excluded ones are in grey.

LCA software and bibliography

The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent v3.10.1 and One Click LCA databases were used as sources of environmental data. Allocation used in Ecoinvent 3.10.1 environmental data sources follow the methodology 'allocation, cut-off, EN 15804+A2'.

Environmental impact data

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

Core environmental impact indicators – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3
GWP – total¹	kg CO ₂ e	2.51E+02	1.70E+01	5.59E+00	2.73E+02
GWP – fossil	kg CO ₂ e	2.51E+02	1.70E+01	5.59E+00	2.73E+02
GWP – biogenic	kg CO ₂ e	1.03E-02	3.17E-02	7.60E-04	4.27E-02
GWP – LULUC	kg CO ₂ e	4.00E-02	1.31E-04	4.57E-04	4.06E-02
Ozone depletion pot.	kg CFC-11e	2.09E-06	2.80E-06	4.93E-08	4.94E-06
Acidification potential	mol H ⁺ e	1.44E+00	6.96E-02	3.61E-02	1.55E+00
EP-freshwater²	kg Pe	5.46E-02	5.59E-04	9.11E-04	5.60E-02
EP-marine	kg Ne	4.04E-01	2.34E-02	7.60E-03	4.35E-01
EP-terrestrial	mol Ne	4.34E+00	2.62E-01	8.05E-02	4.68E+00
POCP (“smog”)³	kg NMVOCe	1.14E+00	8.81E-02	2.46E-02	1.26E+00
ADP-minerals & metals⁴	kg Sbe	1.34E-05	5.45E-05	2.06E-06	7.00E-05
ADP-fossil resources	MJ	1.14E+03	2.18E+02	6.78E+01	1.43E+03
Water use⁵	m ³ e depr.	2.38E+02	1.48E+02	3.69E+01	4.23E+02

Environmental Product Declaration

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Impact category	Unit	C1	C2	C3	C4	D
GWP – total	kg CO ₂ e	4.41E+00	1.25E+01	7.10E+00	4.34E+00	-1.27E+01
GWP – fossil	kg CO ₂ e	4.41E+00	1.25E+01	7.10E+00	4.34E+00	-1.26E+01
GWP – biogenic	kg CO ₂ e	4.50E-04	2.83E-03	-7.24E-04	-1.38E-03	-3.96E-02
GWP – LULUC	kg CO ₂ e	4.52E-04	5.58E-03	7.27E-04	2.48E-03	-1.75E-02
Ozone depletion pot.	kg CFC-11e	6.75E-08	1.84E-07	1.09E-07	1.26E-07	-1.06E-06
Acidification potential	mol H ⁺ e	3.98E-02	4.25E-02	6.41E-02	3.08E-02	-8.26E-02
EP-freshwater	kg Pe	1.27E-04	9.71E-04	2.05E-04	3.57E-04	-7.47E-04
EP-marine	kg Ne	1.85E-02	1.40E-02	2.97E-02	1.17E-02	-1.79E-02
EP-terrestrial	mol Ne	2.02E-01	1.52E-01	3.25E-01	1.28E-01	-2.33E-01
POCP (“smog”)	kg NMVOCe	6.03E-02	6.27E-02	9.71E-02	4.59E-02	-5.99E-02
ADP-minerals & metals	kg Sbe	1.58E-06	3.48E-05	2.55E-06	6.90E-06	-1.27E-04
ADP-fossil resources	MJ	5.77E+01	1.81E+02	9.29E+01	1.07E+02	-1.88E+02
Water use	m ³ e depr.	1.44E-01	8.94E-01	2.32E-01	3.07E-01	-2.50E+01

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionising radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Additional environmental impact indicators – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3
Particulate matter	Incidence	6.89E-06	1.21E-06	8.08E-07	8.91E-06
Ionising radiation⁶	kBq U235e	4.26E-01	0.00E+00	7.08E-02	4.97E-01
Ecotoxicity (freshwater)	CTUe	3.85E+02	5.89E+01	1.08E+01	4.55E+02
Human toxicity, cancer	CTUh	1.83E-08	4.42E-09	4.18E-10	2.31E-08
Human tox. non-cancer	CTUh	5.91E-07	1.71E-07	2.83E-08	7.91E-07
SQP⁷	-	6.59E+02	5.11E+01	1.78E+01	7.28E+02

Impact category	Unit	C1	C2	C3	C4	D
Particulate matter	Incidence	1.13E-06	1.25E-06	1.39E-05	7.00E-07	-1.06E-06
Ionising radiation	kBq U235e	2.56E-02	1.58E-01	4.11E-02	6.70E-02	-2.98E+00
Ecotoxicity (freshwater)	CTUe	3.18E+00	2.56E+01	5.11E+00	8.94E+00	-2.25E+02
Human toxicity, cancer	CTUh	4.53E-10	2.06E-09	7.30E-10	8.00E-10	-1.31E-08
Human tox. non-cancer	CTUh	7.18E-09	1.17E-07	1.16E-08	1.84E-08	-2.40E-07
SQP	-	4.04E+00	1.82E+02	6.51E+00	2.10E+02	-1.81E+02

6) EN 15804+A2 disclaimer for Ionising radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionising radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionising radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

Use of natural resources

Impact category	Unit	A1	A2	A3	A1-A3
Renew. PER as energy ^a	MJ	5.86E+01	2.48E+00	6.35E-01	6.17E+01
Renew. PER as material	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renew. PER	MJ	5.86E+01	2.48E+00	6.35E-01	6.17E+01
Non-re. PER as energy	MJ	1.14E+03	2.29E+02	6.84E+01	1.44E+03
Non-re. PER as material	MJ	3.46E+00	0.00E+00	-1.33E-01	3.32E+00
Total use of non-re. PER	MJ	1.14E+03	2.29E+02	6.83E+01	1.44E+03
Secondary materials	kg	3.08E-02	0.00E+00	0.00E+00	3.08E-02
Renew. secondary fuels	MJ	6.58E-06	0.00E+00	7.35E-05	8.01E-05
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³	3.92E+00	3.45E+00	6.97E-02	7.44E+00

Environmental Product Declaration

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Impact category	Unit	C1	C2	C3	C4	D
Renew. PER as energy	MJ	3.65E-01	2.48E+00	5.88E-01	1.03E+00	-1.85E+01
Renew. PER as material	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renew. PER	MJ	3.65E-01	2.48E+00	5.88E-01	1.03E+00	-1.85E+01
Non-re. PER as energy	MJ	5.77E+01	1.81E+02	9.29E+01	1.07E+02	-1.93E+02
Non-re. PER as material	MJ	0.00E+00	0.00E+00	-2.33E+00	-9.97E-01	2.33E+00
Total use of non-re. PER	MJ	5.77E+01	1.81E+02	9.05E+01	1.06E+02	-1.91E+02
Secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renew. secondary fuels	MJ	6.26E-05	9.79E-04	1.01E-04	5.54E-04	-1.50E-03
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³	3.81E-03	2.68E-02	6.14E-03	1.11E-01	-5.80E-01

8) PER = Primary energy resources.

End of life – Waste

Impact category	Unit	A1	A2	A3	A1-A3
Hazardous waste	kg	1.55E+00	3.03E-04	2.95E-02	1.58E+00
Non-hazardous waste	kg	3.26E+01	2.41E+00	7.73E-01	3.58E+01
Radioactive waste	kg	6.03E-04	1.39E-06	1.15E-05	6.16E-04

Impact category	Unit	C1	C2	C3	C4	D
Hazardous waste	kg	6.42E-02	3.07E-01	1.03E-01	1.18E-01	-1.46E+00
Non-hazardous waste	kg	8.75E-01	5.68E+00	1.41E+00	2.69E+00	-2.71E+01
Radioactive waste	kg	6.27E-06	3.86E-05	1.01E-05	1.63E-05	-3.73E-04

End of life – Output flows

Impact category	Unit	A1	A2	A3	A1-A3
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	3.61E-06	0.00E+00	6.49E+01	6.49E+01
Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Impact category	Unit	C1	C2	C3	C4	D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	1.62E+03	0.00E+00	0.00E+00
Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Environmental impacts – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3
Global Warming Pot.	kg CO ₂ e	2.51E+02	1.69E+01	5.56E+00	2.73E+02
Ozone depletion Pot.	kg CFC ₁₁ e	1.68E-06	2.21E-06	4.16E-08	3.93E-06
Acidification	kg SO ₂ e	1.02E+00	5.26E-02	2.97E-02	1.11E+00
Eutrophication	kg PO ₄ ³⁻ e	3.21E-01	1.13E-02	5.41E-03	3.38E-01
POCP ("smog")	kg C ₂ H ₄ e	3.83E-02	2.12E-03	1.47E-03	4.19E-02
ADP-elements	kg Sbe	1.25E-05	3.73E-05	2.01E-06	5.18E-05
ADP-fossil	MJ	3.25E+02	2.29E+02	6.76E+01	6.21E+02

Environmental Product Declaration

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Impact category	Unit	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	4.39E+00	1.24E+01	7.06E+00	4.30E+00	-1.56E+01
Ozone depletion Pot.	kg CFC ₁₁ e	5.35E-08	1.47E-07	8.61E-08	9.99E-08	-1.08E-07
Acidification	kg SO ₂ e	2.80E-02	3.25E-02	4.51E-02	2.28E-02	-7.50E-02
Eutrophication	kg PO ₄ ³ e	6.54E-03	7.91E-03	1.05E-02	7.24E-03	-1.47E-02
POCP ("smog")	kg C ₂ H ₄ e	2.10E-03	2.90E-03	3.38E-03	2.15E-03	-6.68E-03
ADP-elements	kg Sbe	1.54E-06	3.39E-05	2.47E-06	6.76E-06	-8.56E-05
ADP-fossil	MJ	5.73E+01	1.79E+02	9.22E+01	1.05E+02	-1.93E+02

Additional indicator – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3
GWP-GHG ⁹	kg CO ₂ e	2.51E+02	1.70E+01	5.59E+00	2.73E+02

Impact category	Unit	C1	C2	C3	C4	D
GWP-GHG	kg CO ₂ e	4.41E+00	1.25E+01	7.10E+00	4.34E+00	-1.26E+01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows – CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide – were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterisation factor for biogenic CO₂ is set to zero.

Scenario documentation

Manufacturing energy scenario documentation

Manufacturing energy scenario documentation – A3 (Energy data source)

1. Construction, specialized activities, demolition and site preparation, Market for diesel, burned in building machine, World, ecoinvent 3.10.1, 0.10 kgCO₂e/MJ
 2. Electricity, Electricity, consumption mix w/o renewables, Victoria, 2024, Australia, LCA study for country specific consumption mixes, OneClickLCA 2025, 1.14 kgCO₂e/kWh
- Electricity data source: Australian Energy Update 2024, published by the Department of Climate Change, Energy, the Environment and Water (DCCEEW)

End of life scenario documentation

Collection process – kg collected separately	0
Collection process – kg collected with mixed construction waste	2318
Recovery process – kg for re-use	0
Recovery process – kg for recycling	1620
Recovery process – kg for energy recovery	0
Disposal (total) – kg for final deposition	6.95E+02
Scenario assumptions e.g. transportation	Market for transport, freight, lorry >32 metric ton, EURO5; 50km

Third-party verification statement

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.

Verified tools

Tool verifier: Imane Uald Lamkaddam

Tool verification validity: 28 March 2025 - 27 March 2028



Xinyuan Zhang
Program assistant



The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.